



- Reliable structure, static loading capacity: 300KG
- Simple structure, easy operation, precision size
- Tempered glass front door
- Castor wheels and support feet option are available
- Quick install side panel and rear door for easier maintenance
- The bottom cable entry can be adjusted according to the requirement
- Optional accessories



Model (Size): 4166C (600Wx600Dx2029Hmm)

Door (Front / Back): Mesh Door / Steel Panel

General

Standard	Comply with ANSI/EIA, RS-310-D; IEC297-2; DIN41491: PART 1; DIN41491: PART 7; GB/T3047.2-92 standard Compatible with 19" international standard, metric system and ETSI standard
----------	---

Static loading capacity	300KG
-------------------------	-------

Cable entry	Bottom
-------------	--------

Materials

Update Date: January 10, 2024

Specification subject to change without notice

EIGHT LIMITED

No.18, 4/F., Thriving Industrial Centre, 26-38 Sha Tsui Road, Tsuen Wan, Hong Kong

TEL: (852) 2413 2222

FAX: (852) 2411 3000

EMAIL: info@eightgroup.com

Panel	SPCC cold rolling steel plate
-------	-------------------------------

Mounting profile thickness	1.5mm
----------------------------	-------

Others panel thickness	0.8mm
------------------------	-------
