



- Reliable structure, static loading capacity: 60KG
- Simple structure, easy operation, precision size
- Tempered glass front door
- Castor wheels and support feet option are available
- Quick install side panel and rear door for easier maintenance
- The bottom cable entry can be adjusted according to the requirement
- Optional accessories



Model (Size): 1566WM (600Wx600Dx775Hmm)

Door (Front / Back): Glass Door / Steel Panel

General

| | |
|----------|---|
| Standard | Comply with ANSI/EIA, RS-310-D; IEC297-2; DIN41491: PART 1; DIN41491: PART 7; GB/T3047.2-92 standard Compatible with 19" international standard, metric system and ETSI standard |
|----------|---|

| | |
|-------------------------|------|
| Static loading capacity | 60KG |
|-------------------------|------|

| | |
|---------------|----------------|
| Cable entries | Top and bottom |
|---------------|----------------|

Materials

Update Date: January 09, 2024

Specification subject to change without notice

EIGHT LIMITED

No.18, 4/F., Thriving Industrial Centre, 26-38 Sha Tsui Road, Tsuen Wan, Hong Kong

TEL: (852) 2413 2222

FAX: (852) 2411 3000

EMAIL: info@eightgroup.com

| | |
|-------|-------------------------------|
| Panel | SPCC cold rolling steel plate |
|-------|-------------------------------|

| | |
|----------------------------|-------|
| Mounting profile thickness | 1.5mm |
|----------------------------|-------|

| | |
|------------------------|-------|
| Others panel thickness | 0.8mm |
|------------------------|-------|
