



- 導體：28 AWG
- 標準：ISO/IEC 11801、ANSI/TIA-568-C2
- 應用：數據通訊、本地網絡、樓宇信號系統
- ISO9001認證製造工廠



長度: 1米

型號: PC5_M_1

Standard

Standard	ISO/IEC 11801, ANSI/TIA- 568-C2 ISO9001Certified Manufacturing Plant
----------	---

General

Conductor	Material	Stranded-Bare Copper
	Nom. O.D. (mm)	28AWG (7/0.12)
Insulation	Material	HDPE
	Diameter	0.58±0.05 mm
Sheath	Thickness	0.55±0.05 mm
	External O.D.(Avg.)	3.8±0.3mm
	Surface	Clean, Frap, Satiation
	Material	PVC (complies RoHS)

Update Date: July 08, 2024

Specification subject to change without notice

Sheath Physical Properties (Before Aging)	Tensile Strength (Mpa)	≥13.5
	Elongation (%)	≥150
	Aging Period (°C x hrs)	100°C x 24h x 7d
Sheath Physical Properties (After Aging)	Tensile Strength (Mpa)	≥12.5
	Elongation (%)	≥125
	Cold bend (-20±2°C x 4h)	No visible cracks
Electrical Characteristics (20°C)	Impedance (Ω)	100±15
	Delay Skew (ns/100m)	≤45
	DC Resistance (Ω/100m)	23.7

Electric Performance

Frequency (MHz)	Attenuation (dB/100m)	Next (dB)	Return Loss (dB)	Delay (ns)	ELFEXT (dB)	Power Sum Next (dB)	Power Sum Delay (ns)
1	3	60	19	521	58.6	57	55.6
4	3.9	54.8	19	504	46.6	51.8	43.6
8	5.5	50	19	500	40.6	47	37.5
10	6.2	48.5	19	498	38.6	45.5	35.6
16	7.9	45.5	19	496	34.5	42.2	31.5
20	8.9	43.7	19	495	32.6	40.7	29.6
25	10	42.1	18	495	30.7	39.1	27.7
31.25	11.2	40.5	17.1	494	28.7	37.5	25.7

62.5	16.2	35.7	14.1	492	22.7	32.7	19.7
100	21	32.3	12	□491	18.6	18.6	15.6
