



Outdoor Slim Fiber Terminal Box FTMB-SLIM Series

Features

- Water-proof design for outdoor uses
- Ready for wall mount – installation kits provided
- Double-layer design for easier installation and maintenances
- Lower layer for splitters and over length fiber storage
- Upper layer for splicing, cross-connecting and fiber distribution
- Cable fixing units provided for fixing the outdoor optical cable
- Accommodates both cable glands as well as tie-wraps
- Lock provided for extra security



Specifications

Specification	FTMB-SLIM-6D
For Number of Couplers	Up to 6
Max Capacity	6 cores SC / 12 cores LC
Working Temperature	-40°C~+85°C
Relative Humidity	<85% (+30°C)
Atmospheric Pressure	70Kpa~106Kpa
Insertion Loss	<0.2db
UPC Return Loss	>50db
APC Return Loss	>60db
Life of Insection and Extraction	>1000 times
Size	215 x 140 x 40 mm

How to Order :

MODEL	FTMB-SLIM-	XX	D	-	XX	-	XX	X
No. Of Couplers	Adapter	MODE	CONNECTOR	POLISH				
I-6	D : Duplex	SM : Single Mode MM : Multi-mode	1) SC 2) LC 3) FC 4) ST	A : APC P : PC U : UPC				

Remember to State :

1) Number of Core(s) 2) Type of Coupler 3) Mode of fiber