



Features

- Supreme quality
- Intercom / PA systems
- Sound / Audio systems
- LSZH Jacket option available

Microphone Cable



Specifications

Model		1625	1810	2512
Conductor	Material	TC	BC	BC
	Cores	2	2	2
	Max Resistance(20°C)	24.5Ω/km	125Ω/km	63Ω/km
	Construction(No./mm)	16/0.25mm	18/0.1mm	25/0.12mm + 1 Tinsel copper
Insulation	Insulation	PE	PE	PVC
	Insulation Dielectric	2.2mm±0.1mm	1.05mm±0.1mm	1.7mm±0.1mm
	Insulation Color	White & Transparent	White & Orange	Red & White
Filler	Material	/	Cotton Yarn & Cotton paper	Cotton Yarn
Shield	AL Foil	AL Foil	/	AL Foil
	Braid(No./mm)	/	71/0.1mm TC	96/0.01mm BC
	Drain wire(No./mm)	10/0.25TC	/	/
Jacket	Jacket Material	PVC	PVC	PVC
	Jacket Color	Grey	Black	Black
	Jacket Thickness	0.65mm	1.0mm	1.1mm
	Jacket O.D	5.5mm±0.2mm	4.5mm±0.2mm	6.5mm±0.2mm
Operation Temperature		-20°C To +60°C	-20°C To +60°C	-20°C To +60°C
Suitable for		Indoor	Indoor	Indoor
Diameter	100 Yards	Φ220x101mm	---	Φ220x136,
	200 Yards	Φ220x196mm	---	Φ240x206
Weight		200 Yards: 7.78Kg	---	100 Yards: 5.22Kg
Construction				

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.