



NVR with SATA EIR-H1032

Features

- 32 Channel NVR with 2 SATA Bays
- Support HDMI 4K output VGA HD output
- Support ONVIF; access third party Support web, CMS, center platform management software
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.)

Specifications

Model		EIR-H1032
System & Interface	Main processor	Hi3536C
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1 / 4 / 9 / 16 / 32
Video	Video input (IP)	32x4K / 32x5M / 32x1080P
	Access bandwidth	300Mbps
	Forwarding bandwidth	240Mbps
	Video compression	H.265/H.264
	Display quality	Max:4K
	Playback quality	4K / 5M / 1080P
	Decode	1x4K / 2x5M / 4x1080P
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	support
Record & Playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	1x4K / 2x5M / 4x1080P
	Search mode	Search by Time / Calendar / Event / Channel
	Record storage	HDD 、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA 、 1ch HDMI HD output
	Audio I/O	1 / 1
	Alarm I/O	0 / 0
	Network interface	1xRJ45 10M / 100M / 1000M Adaptive Ethernet port
	USB interface	2xUSB2.0 portsx
	HDD	2 SATA (Up to 8TB for each disk)
	ESATA	No
	Serial interface	No
General	ONVIF	Support
	Power supply	12V / 4A
	Power Consumption	<10W (Without HDD)
	Work Temperature	0°C~+55°C
	Work Humidity	10%~90%RH
	Work Atm	86kpa~106kpa
Dimension (LxWxH)	335 x 255 x 50mm	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.